

RAPIX

RAPIX DALI-2 Occupancy Sensor Range



Technical Overview Guide
February 2024



Engineered by
ozuno

sales@ozuno.com

www.ozuno.com

RAPIX DALI-2

Movement and Light Level Sensor

Designed and developed in Australia




The RAPIX Movement and Light Level Sensor can act as a miniature application controller for its own built-in sensing functions, with passive infrared movement sensing, light level sensing, and a voltage-free input.

This sensor can detect common movement operations as well as being used for light level sensing and light level maintenance to manage the daylight harvesting of a lighting system. As an added feature, the design team incorporated a voltage free input to allow for switching and control functions.


This sensor can be used in any DALI-2 system. It can also act as a miniature DALI-2 Application Controller. Multiple sensors can easily be used to expand coverage to larger areas. For further scalability the sensor can be mixed on a line with other RAPIX products such as the Four Channel Zone Controller, DALI-2 Switch range and other sensors.

Detection Range:

DALI-2 Movement Sensor



DALI-2 Long Range Movement Sensor



Voltage free contact input for direct connection to switches and sensors


Light level sensor 0-65000 lux

LED indicator for easy identification during commissioning



Generous terminal size with clear cover for easy inspection

Low profile lens providing a discreet finish when installed on white ceilings



Available Models:



DALI-2 Movement and Light Level Sensor
DGOZ-SEN-PRLLSW



DALI-2 Movement and Light Level Sensor
DGOZ-SEN-PRLLSW-BK



DALI-2 Movement Sensor
DGOZ-SEN-PRSW



DALI-2 Long Range Movement and Light Level Sensor
DGOZ-LRS-PRLLSW



DALI-2 IP65 Long Range Movement and Light Level Sensor
DGOZ-SEN-PRLLSW-IP




DALI-2 Miniature Movement and Light Level Sensor
DGOZ-SEN30-PRLLSW

Think DALI-2 - think RAPIX



An Application Controller

Hidden inside for built-in functions





Accessories:



Features:

- Only 4 mA current drawn from DALI.
- External sensors with voltage-free contacts suits all switch types and voltage free motion sensors.
- Configured using the RAPIX Addressing, Integrator or any other DALI commissioning software.
- Surface mount adaptor available, suited to 50 mm and 60 mm screw mounting centres.

Dimensions:



RAPIX - Worlds lowest power DALI-2 Occupancy Sensors





RAPIX

LIGHTING
CONTROL SYSTEM

Contact Us

 sales@ozuno.com

 www.ozuno.com



ozuno



Version 1 February 2024
Copyright © Ozuno Holdings Pty Ltd